


CAT6 1000' STRANDED UTP NETWORK BULK CABLE

SKUS PW-608

FEATURES

- Category 6 UTP Stranded Copper Data Communications Cable 1000' 24 AWG
- Use in indoor installations for voice, data, video distribution, and security applications
- Stranded cabling provides greater bendability and flexibility when compared to solid copper core cabling
- Suitable for 550MHz Giga Speed Data Applications and Fast Ethernet
- Excellent Attenuation and Crosstalk Characteristic
- Constructed with a spline separating individual twisted pairs, decreasing crosstalk and allowing greater speeds over longer distances
- 4-Pair Identified Colour-Striped Pairs
- Meets or exceeds EIA/TIA 568 B.2-1, UL, CSA and ISO/IEC 11801 specifications
- Supplied in Easy to handle 1000' Reel Pull Boxes



CONSTRUCTION

| CONDUCTOR | Stranded Bare Copper |
|---|----------------------|
| 4 TWISTED PAIRS | 8C |
| AWG | 24 |
| CONSTRUCTION (±0.008mm) | 7/0.20 |
| STRANDED DIA. (mm) | 0.61 |
| INSULATION | HD PE |
| NOM. THICKNESS (mm) | 0.18 |
| INSULATION DIA. (±0.05mm) CABLED TOGETHER, PUTTING SEPARATOR X(PE) ACROSS | 0.97 |
| JACKET | PVC |
| NOM. THICKNESS (mm) | 0.59 |
| OUTER DIA. (±0.2mm) | 6.0 |



AVAILABLE COLOURS









DESCRIPTION

| RATED TEMPERATURE | 75°C |
|--------------------------------|---|
| RATED VOLTAGE (V) | - |
| PRODUCT STANDARD CERTIFICATION | UL CM & CSA CMG |
| FLAME TEST | FT4 |
| APPLICATION | Telephone and other communication circuits such as voice, data, and audio for on-premise customer systems |
| REFERENCE STANDARD | UL 444 |

COLOUR

| INSULATION | P1: Blue & White/Blue P2: Orange & White/Orange |
|--------------|--|
| CORES: PAIRS | P3: Green & White/Green P4: Brown & White/Brown |

| PERFORMANCE | | |
|--|---------------|--|
| ELECTRICAL CHARACTERISTICS (20°C) | | |
| MAX. CONDUCTOR DC RESISTANCE (Ω/km) | #24:89 | |
| MIN. INSULATION RESISTANCE (Ω/m) | HD PE:100M | |
| DIELECTRIC STRENGTH | AC-500V/1 Min | |
| MECHANICAL CHARACTERISTICS | | |
| TEST OBJECT / MATERIAL | Jacket / PVC | |
| BEFORE TENSILE STRENGTH (kgf/mm²) | ≥1.05 | |

PC Cable World product specifications are subject to change without notice, but are accurate at the time of printing. Please contact a sales representative for current specs. Please note that all physical specifications are nominal.

[©] PC Cable World. All rights reserved.