



LC/APC-SC SM SIMPLEX 9/125 FIBER OPTICAL CABLE

SKUS	LCASC03SS (3')	LCASC33SS (33')
	LCASC06SS (6')	LCASC50SS (50')
	LCASC10SS (10')	LCASC65SS (65')
	LCASC15SS (15')	LCASC75SS (75')
	LCASC25SS (25')	LCASC100SS (100')



FEATURES

- LC/APC-SC/UPC OM2 Single-Mode Simplex Cable 9/125µm
- Perfect for fast Ethernet, gigabit Ethernet, and other data applications
- Ideal solution for long-range networking
- UL listed and OFNR (riser) rated
- Suitable for use in upright shafts between building floors
- Compliant with ITU-T standard G657A1
- Features a standard SMF yellow jacket and Corning core
- Each cable is individually packed in a zip bag for convenience



MATERIALS

(1)	OD: 2.0mm, Singlemode 9/125 G657A1, Corning Fiber, Simplex Cable, PVC, Colour: Yellow
(2)	LC/APC SM 2.0mm Simplex Connector (Green Housing Green Boot)
(3)	SC/UPC SM 2.0mm Simplex Connector (Blue Housing Blue Boot)

CABLE LENGTH AND TOLERANCE

CABLE LENGTH<1M	5cm
1M≤CABLE LENGTH<15M	10cm
15M≤CABLE LENGTH<30M	15cm
CABLE LENGTH≥30M	Cable Length*1%

SPECIFICATIONS

INSERTION LOSS	≤ 0.3 dB
RETURN LOSS	≥ 60 dB (APC), ≥ 55 dB (UPC)

© PC Cable World. All rights reserved.

PC Cable World product specifications are subject to change without notice, but are accurate at the time of printing. Please contact a sales representative for current specs. Please note that all physical specifications are nominal.